



**F&J SPECIALTY PRODUCTS, INC.**

*The Nucleus of Quality Air Monitoring Programs*

---

## **PORTABLE DIGITAL FLOWMETER KIT for ENVIRONMENTAL STYLE AIR SAMPLERS DF-100/DF-100E SERIES**



### **GENERAL DESCRIPTION:**

The DF-100 Series portable flowmeter upgrade kits are designed to upgrade existing air sampling systems utilizing motors of 1/3 HP or less. The DF-100 units are connected in-line between the pump inlet and the filter holder. The DF-100 Series upgrade eliminates the need to engage in expensive conversions of equipment or the need to purchase new air sampling systems.

The typical operating flow ranges vary from 1 CFM to 9 CFM (30 – 255 LPM). Custom higher flow ranges with exterior mounted flow sensors are available upon request.

### **OPTIONS:**

Data Storage Device	(P/N: 232FCDS)
2+ GB Secure Digital Card	(P/N: 372239)
Flashcard Reader	(P/N: SDDR-199-A20)

**REV:** 30 July 2015

## NOTABLE FEATURES:

- Display in English or metric units set at factory
- Choices of flow/volume units:
  - scm      scc
  - SLPM    SL
  - SCMH    SCM
  - SCFM    SCF
- State of the Art microprocessor electronics
- Flowrate and volume totalizations displayed are corrected to a factory settable Reference Temperature and Pressure (4 options available)
  - Classical STP                      0°C, 760 mmHg
  - Normal T and P                      20°C, 760 mmHg
  - Modified Normal T and P          21,1°C, 760 mmHg
  - Standard Ambient T and P        25°C, 760 mmHg
- Elapsed time meter
- Auto zero calibration feature of flow sensor
- Bright LED display
- Flow rate accuracy within  $\pm 4\%$  F.S.
- RS-232 Communication Port w/Operator selectable download frequency for real-time data
- Auto Shut-off on time or volume
- **DF-100:**
  - 110 – 120VAC, 50/60Hz; single phase; < 7.20 FLA\*
- **DF-100E:**
  - 220 – 240VAC, 50/60Hz; single phase; < 3.24 FLA\*

\* FLA = Full Load Amps

**F&J SPECIALTY PRODUCTS, INC.**

**Tel: (352) 680-1177 / Fax: (352) 680-1454 / Email: [fandj@fjspecialty.com](mailto:fandj@fjspecialty.com)**

## DF-100 SERIES Portable Digital Flowmeter Kit for Air Samplers

---

### SPECIFICATIONS:

#### Flow Range Available:

Model	Model	Flow Range	
110-120 VAC	220-240 VAC	(CFM)	(LPM)
DF-100-30L	DF-100E-30L	0.1 – 1	3 – 30
DF-100-60L	DF-100E-60L	0.2 – 2	6 – 60
DF-100-115L	DF-100E-115L	0.5 – 4	14 – 115
DF-100-250L	DF-100E-250L	1 – 9	30 – 255

#### Power Requirements:

##### DF-100 Series:

110 – 120 VAC, 47-63 Hz; 0.3 amperes maximum

##### DF-100E Series:

220 – 240 VAC, 47-63 Hz; 0.2 amperes

#### Maximum Motor Rating:

Model	HP	FLA
DF-100	1/3	7.20
DF-100E	1/3	3.24

**Fuse Protection (for plugged in sample):** 8 amp, slow blow

**Electrical Cord:** 3 wire, 16 gauge

**Dimensions:** 8" L x 8" W x 12" H. (20,3L x 20,3W x 30,5 cm H)

**Weight:** 4.1 lbs. (1864 gms.)

**Installation Category:** Pollution Degree 2

### ELECTRONIC SPECIFICATIONS:

#### Measurement Accuracy:

Air flow	± 4% of full scale
Temperature	± 2.0° F (1.1° C)
Barometric Pressure	2% over measured range

**Operating Temperatures:** 0° to 122° F (-17° to 50° C)

**Storage Temperature:** 0° to 158° F (-17° to 70° C)

**Calibration:** Calibration-Verification once per year

**Communications Interface:** RS-232 (comma delimited text file)


**Display:** LED; 6 character

### On-Board Calculations:

- Flow calculation from differential pressure value using best-fit curve method.
- Flow correction for standard temperature and pressure
- Auto-zero correction utilizing electro-pneumatic method to compensate for offset and drift (automatic once every minute).

**F&J SPECIALTY PRODUCTS, INC.**

**Tel: (352) 680-1177 / Fax: (352) 680-1454 / Email: [fandj@fjspecialty.com](mailto:fandj@fjspecialty.com)**



# F&J SPECIALTY PRODUCTS, INC.

*The Nucleus of Quality Air Monitoring Programs*

## PRODUCT PROFILE

### Air Sampling Systems

- ❖ High Volume Air Samplers
  - Portable Grab Samplers
  - Environmental Systems
  - Enzyme Dust Samplers
  - PM10 Systems
- ❖ Continuous Air Samplers
  - Environmental Systems
  - Portable
  - Fixed Station
- ❖ Personal Air Samplers
- ❖ Emergency Response DC Powered Air Sampling Systems

### Filter Paper

- ❖ Glass Fiber
- ❖ Cellulose
- ❖ Membrane
- ❖ Quartz

### Filter Holders

- ❖ Open face
- ❖ In-Line
- ❖ Lapel Monitors
- ❖ Materials
  - Plastic
  - Aluminum
  - Stainless Steel

### Radon Detection Devices

- ❖ 2-Day Passive Charcoal Canisters
- ❖ 7-Day Passive Charcoal Canisters
- ❖ Continuous Radon Monitors

### Tritium Detection Systems

- ❖ Portable and Fixed Station Collection Systems utilizing Silica Gel or Molecular Sieve Absorbents
- ❖ Continuous Tritium Monitors

### New Products

- ❖ Global Air Sampling Systems
- ❖ Digital Flowmeter Air Samplers
- ❖ C-14 Collection Systems
- ❖ ELITE DIGITAL LIGHT (EDL) Air Samplers
- ❖ Isokinetic Air Sampling Systems
- ❖ MEGA High Volume Air Samplers
- ❖ ULTRA High Volume (CTBTO) Air Samplers

### Radioiodine Collection Cartridges

- ❖ TEDA Impregnated Charcoal
- ❖ Silver Zeolite
- ❖ Custom Cartridges
- ❖ Bulk Silver Zeolite

### Air Flow Calibrators

- ❖ World Calibrator Series
- ❖ Compact Digital V.2 Series
- ❖ Bubble Calibrators for Personal Air Samplers