



LOW VOLUME AIR SAMPLING SYSTEM DIGITAL FLOW METER TECHNOLOGY F&J Model DFCB-100L-AC

NOTABLE FEATURES:

- State-of-the-Art Electronics
- Operating Modes
 - Line Power (100VAC – 250 VAC)
 - External Auxiliary DC Power Input
- Lightweight — 6 lbs. (2.7 kg)
- Maximum Flow 100 LPM with 521147 HEPA Glass Fiber Filter Paper
- Bright OLED Display; 4 Line x 32 characters
- Automatic Flow Control Feature
- Flowrate and Volume totalizations displayed are corrected to a factory settable Reference Temperature and Pressure (4 options available)
- Auto shut-off on time or volume
- Brushless Motor
- High Speed Centrifugal Blower
- Internal Data Storage Downloadable as (.csv) file
- Data Download via Bluetooth with Optional Bluetooth Dongle for PC Device



**Unit shown with optional
filter holder FJ-34**

GENERAL DESCRIPTION:

F&J Model DFCB-100L-AC is a lightweight, small footprint, DC voltage powered air sampling system operable from (1) line power, or (2) the auxiliary DC connector (12 – 15 VDC)

The DFCB-100L-AC is well suited for standard low volume air sampling and emergency response sampling activities where users have line power available.

The automatic flow control feature with the F&J Digital Flowmeter technology provides maximum flexibility for emergency response sampling responsibilities. The set flowrate is maintained automatically in case of dust loading and does not require operator attention. The air sampler is contained in a lightweight small dimensioned metal enclosure. The unit can be carried very easily by its large, rugged handle.

Typical flow range is 15 - 100 SLPM (0.5 — 3.5 SCFM).

The air sampler is also equipped with internal data storage that allows user to download the sampling data as a .csv file for easy data analysis.

REV: 04 April 2024

DFCB-100L-AC / DC Air Sampler Specifications

Pump Type: High efficiency centrifugal blower

Motor: Brushless 12VDC

Maximum Flowrate: 100 LPM typical
with 521147 HEPA glass fiber media

Power Source:
External – Line Power; 100VAC to 240VAC
External Auxiliary DC Power Input (12—15VDC)

Current Draw: 8.0 A maximum on 12VDC
1.0 A on line power

Filter Holder Fitting: 1.83—12 U.N.F (Air Sampler)
1.80—12 U.N.M (Filter Holder)

Handles: Durable plastic; multiple handles

Weight: 6 lbs. (2.7 kg)

Dimensions: 8”L × 6”W × 8”H
(20 × 15 × 20 cm)

Average Db: @ 1 meter

Operating Temperature Range: 18°F to 122°F
(-10°C to 50°C)

Display: Bright OLED (4 line x 32 character)

Elapsed Time: DD:HH:MM up to 168 hours

Flow Control:
Adjustable from keypad between 15-100 LPM

Flow Accuracy: ±4.0% of Full Scale

Factory Settable Reference T and P

Classical STP	0°C, 1 ATM
Normal T and P	20°C, 1 ATM
Modified Normal T and P	70°F, 1 ATM
Standard Ambient T and P	25°C, 1 ATM

OPTIONS:

- Bluetooth Dongle for PC Device (P/N: BTDG)

Standard Combination Plastic Filter Holders Available:

FILTER HOLDER MODEL	CHARCOAL CARTRIDGE DIMENSIONS	PARTICULATE PAPER DIAMETER
FJ-19	F&J Model C	2” or 50 mm
FJ-27	F&J Model B	2” or 50 mm
FJ-34	F&J Model C	47 mm
FJ-39	F&J Model B	47 mm
FJ-52	F&J Model M	2” or 50 mm
FJ-54	F&J Model M	47 mm

Available Engineering Units for Flow and Volume:

- SLPM / SLP
- SCFM / SCF
- SCMH / SCM

Digital Flow Meter Keypad/Display

