

F&J SPECIALTY PRODUCTS, INC.

The Nucleus of Quality Air Monitoring Programs

EMERGENCY RESPONSE MOBILE HIGH VOLUME AIR SAMPLING SYSTEM MODEL GAS-ERHV-DTE-CFH

NOTABLE FEATURES:

- Precision machined DP flow sensor
- State-of-the-Art electronics (CE approved)
- Vacuum fluorescent display (VFD); 4 lines×24 characters
- Flow rate and Volume measurements corrected to operator selectable Reference Temperature and Pressure
- Automatic flow control
- Operator selectable units of measurement
- Dual RS-232 communication ports, or one RS232 and one USB
- Flow rate accuracy: ±3.0% Full Scale
- Auto zero calibration feature of flow sensor
- Continuous or periodic sampling mode
- Multiple operator selectable data storage rates
- Display of Multiple on-board calculations
- Powerful 1100 Watt motor (CE approved)
- Meets or exceeds the USEPA requirements in 40CFR50 Appendix B
- 220-240VAC; 50/60Hz, single phase



GAS-ERHV-DTE-CFH
Global Air Sampler
Electronic Flow Management System
Mobile High Volume Air Sampler
for
Circular Filter Media

GENERAL DESCRIPTION:

The GAS-ERHV-DTE-CFH Series Air Sampling Systems are designed for temporary or emergency response continuous air sampling applications. The GAS-ERHV-DTE-CFH Series Air Samplers feature a brushless motor with electronic motor speed control that maintains a user selectable flow rate. The flow rate range attainable through the filter media is dependent upon the air porosity of the filter media and filter media dimensions. The GAS-ERHV-DTE-CFH Series design accommodates rapid field service and component replacement.

For mobility, the air sampler is housed in a rugged weather resistant polypropylene enclosure with wheels and multiple handles. The tripod, accessories and consumables are stored in an identical heavy duty polypropylene case. The air sampler is connected to the discharge port of the filter holder mounted on the tripod by a rugged flexible plastic hose. The GAS-ERHV-DTE-CFH model utilizes a circular filter holder that has circular filter media. Filter holder options include 102mm, 110mm, 120mm, 125mm, 130mm, 140mm and 150mm.

The electronic flow control measurement sub-system of the GAS-ERHV-DTE-CFH Series provides an operator selectable reference standard corrected flow measurement and a constant flow of air through the filter medium. The air flow rate is measured by a precision-machined DP sensor. The flow rate obtainable depends on the filter paper air flow resistance and dimensions. The bright VFD readout displays multiple air sampling information including current flow rate, average flow rate, current temperature and totalized volume. Optional software is available to download air-sampling data via an RS-232 port. The software provides a monitoring report, file creation and setup via a laptop computer.

REV: 02 February 2023

Performance:

Basic components of the system are modular and independently serviceable.

Technology: Microprocessor controlled state-of-the-art electronics; CE approved

Operating Temperature Range: 0°F* to 122°F (-17°C* to 50°C)
* warm start/continuous operation

Operating Relative Humidity: 0 – 95% RH

Typical Flow Rate Range: Varies with specific filter media type and dimensions

Motor: Brushless: CE approved 1.5 H.P. (1100 Watt) motor with electronic motor speed control

Power: 220-240VAC; 50/60Hz; 6 amperes; single phase.

Housing: Heavy duty polypropylene case with strong ABS latches and wide-track polyurethane Wheels. Features stainless steel pins, hardware, and padlock protectors.

Dimensions Case 1 & 2: [48.00in x 17.00in x 14.00in (121.92cm x 43.18cm x 35.56)]

Weight: 58 lbs. (26.4 kgs.) Case 1; 40 lbs. (18.1 kgs.) Case 2

Shipping Weight: 75 lbs. (34.0 kgs.) Case 1; 50 lbs. (22.7 kgs.) Case 2

Installation Category: Pollution Degree 3

Enclosure Rating: IPX3

Automatic Flow Control:

The system microprocessor monitors flow rate relative to the operator selectable preset Reference T and P corrected flow rate established during the setup procedure and electronically adjusts the electronic motor speed adjustment, if necessary, to maintain the flow within $\pm 3.0\%$ of setting. The microprocessor computes the Reference flow rate by correcting the measured values of temperature and pressure to the reference values.

On-Board Measurement, Calculations and Other System Features

Measurements:

- Temperature of air flow through system
- Inlet pressure to the flow sensor
- Differential Pressure of the flow sensor
- Ambient pressure

Calculations/Determinations:

- Totalized volume, STP
- Current flow rate, STP
- Minimum and maximum temperature
- Minimum and maximum inlet pressure
- Elapsed time
- Selectable ambient flow rate and volume

Optional Items:

- Optional data acquisition software to download data from instrument to PC after completion of sampling activity
- Ruggedized Cellular Telephone

Other System Features:

- Display of data in English or metric units by selection
- Automatic shut off of system on totalized volume or elapsed time
- Real time clock with battery backup
- Various data storage options
- Dual password protection
Operator password
System Administrator password
- Periodic sampling scenario based on periods within a week selectable by the user
- Circular filter media: Filter holder options include 102mm, 110mm, 120mm, 125mm, 130mm, 140mm and 150mm.
- Vacuum Fluorescent Display; 4lines \times 24 characters
- Operator Selectable Temperature & Pressure for data correction to standard condition.
- Dual RS232 and one USB (Type B) communication ports

Filter Holder Options (Aluminum)

Diameter	Part Number
102 mm	FJ-102MM-HV
110 mm	FJ-110MM-HV
120 mm	FJ-120MM-HV
125 mm	FJ-125MM-HV
130 mm	FJ-130MM-HV
140 mm	FJ-140MM-HV
150 mm	FJ-150MM-HV



**Filter Holder
Standard Design**


Photo Gallery



Sample Inlet



**Sample Inlet
Without Cover**



PRODUCT PROFILE

Air Sampling Systems

- High Volume Air Samplers
 - Portable Grab Samplers
 - Environmental Systems
 - Enzyme Dust Samplers
 - PM10 Systems
- Continuous Air Samplers
 - Environmental Systems
 - Portable
 - Fixed Station
- Personal Air Samplers
- Emergency Response DC Powered Air Sampling Systems

Filter Paper

- Glass Fiber
- Cellulose
- Membrane
- Quartz

Filter Holders

- Open face
- In-Line
- PAS Filter Holders
- Materials
 - Plastic
 - Aluminum
 - Stainless Steel

Radon Detection Devices

- 2-Day Passive Charcoal Canisters
- 7-Day Passive Charcoal Canisters
- Continuous Radon Monitors

Tritium Detection Systems

- Portable and Fixed Station Collection Systems utilizing Silica Gel or Molecular Sieve Absorbents
- Continuous Tritium Monitors

New Products

- Global Air Sampling Systems
- Digital Flowmeter Air Samplers
- C-14 Collection Systems
- ELITE DIGITAL LIGHT (EDL) Air Samplers
- Isokinetic Air Sampling Systems
- MEGA High Volume Air Samplers
- ULTRA High Volume (CTBTO) Air Samplers
- JUNIOR CTBTO Air Samplers

Radioiodine Collection Cartridges

- TEDA Impregnated Charcoal
- Silver Zeolite
- Custom Cartridges
- Bulk Silver Zeolite

Air Flow Calibrators

- World Calibrator Series
- Compact Digital V.2 Series
- Mini-Calibrator