



F&J SPECIALTY PRODUCTS, INC.

PO Box 2888

Ocala, Florida 34478-2888

Tel: (352) 680-1177 • (352) 680-1178

Fax: (352) 680-1454

Email: fandj@fjspecialty.com Internet: www.fjspecialty.com

The Nucleus of Quality Air Monitoring Programs

QR200 Filter Paper Specifications

Applications / Characteristics:

Increased chemical resistance used to monitor airborne particulates. Does not adsorb acid gases.

Weight:	200 gm/m ²
Thickness:	1.0 mm
Pore Size:	1.5 microns
Water Flow Rate:	Not Applicable
Gas Collection Efficiency: (0.3 micron DOP)	99.99%
Pressure Drop:	35mm H ₂ O/5cm/sec.
Binder:	Inorganic
Maximum Temperature:	1000°C

General Properties:

- **Highly resistant** to chemical attack, biologically inert
- **High Purity:** Very low trace metal content, does not adsorb nitrous and sulfur dioxides; Grade QR-200 is pre-fired at 1000°C for 2 hours to reduce organic contamination
- **Easily sterilized:** Can be baked or autoclaved
- **Store indefinitely:** Unaffected by humidity

Applications:

- Sample acidic gases at high (>500°C) temperatures
- Air pollution analysis